DECLARATION OF PERFORMANCE

No. 64030-a-CPR_2021.11.1

Unique identification code of the product-type	EUROTHANE SILVER	
Intended use/es	Thermal insulation for buildings	
Manufacturer	Recticel NV - Zuidstraat 15 - B-8560 Wevelgem	
System/s of AVCP	AVCP 3	
Harmonised standard	EN 13165:2012 + A2:2016	
Notified body/ies	Notified testing laboratory No. NB 1136 & NB 0071 determined the production type under system AVCP3.	

Essential characteristics	Performance		
	(The letters 'NPD' (No Performance Determined) are indicated where no performance is declared.)		
Reaction to fire	Reaction to fire	F	
Reaction to fire – end use	Reaction to fire – end use	B-S2-d0	
Thermal resistance	Thermal resistance (R _D in m²K/W)	1,35 for d _N 30mm	
		9,05 for d _N 200mm	
	Thermal conductivity (λ _D in W/mK)	0,022	
Thickness	d _N : 30 - 200 mm	T2	
Compressive strength	CS(10/Y)150		
Tensile strength/shear behaviour	Tensile strength perpendicular to faces:	TR80	
, and the second	Shear strength:	NPD	
	Shear modulus:	NPD	
Water permeability	Water absorption		
. ,	- short term by partial immersion	NPD	
	- long term by partial immersion	NPD	
	- long term by total immersion	WL(T)2	
	Flatness after one-sided wetting	NPD	
Water vapour permeability	Water vapour transmission	NPD	
Acoustic absorption index	Sound absorption	NPD	
Direct airborne sound insulation	Sound absorption	NPD	
index			
Continuous glowing combustion	No harmonized test method available		
Release of dangerous substances to	No harmonized test method available		
the indoor environment			
Durability of reaction to fire against	Reaction to fire does not change with time		
heat, weathering, ageing /	·		
degradation			
Dimensional stability under specified	48h, 70°C, 90% R.H.	DS(70,90)3	
temperature and humidity conditions			
,	48h, -20°C	DS(-20,-)1	
Deformation under specified	40 kPa, 70°C, 168h	DLT(2)5	
compressive load and temperature	, -,		
conditions			
Compressive creep		NPD	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

at Wevelgem on November 1st 2021

Wim Giebens – Industrial Manager Recticel Building Insulation

Wim Giebens - Industrial Manager Recticel Building Insulation



